

# Chrysalite LED

Patient Room Wall Light



Interior

Patient Room Wall Light

CHRYSLITE LED

Healthcare Lighting • 3 Kilmer Road • Edison, NJ 08817 • 855.868.6980 • f 855.868.6981 • [www.healthcare-lighting.com](http://www.healthcare-lighting.com)

© 2013 Acuity Brands Lighting, Inc. All Rights Reserved. "Healthcare Lighting", "Chrysalite" are registered trademarks of Acuity Brands Lighting. Products herein may be covered by one or more U.S. Patents and Patents Pending. Specifications subject to change without notice. Five-year limited warranty. Complete warranty terms located at: [www.AcuityBrands.com/CustomerResources/Terms\\_and\\_Conditions.aspx](http://www.AcuityBrands.com/CustomerResources/Terms_and_Conditions.aspx)

# Chrysalite LED

Patient Room Wall Light



The Chrysalite LED is a stylish alternative solution for wall-mounted patient bed lighting. Photometric testing shows that fixture placement above and behind the patient delivers optimum light for reading and tasks. The Chrysalite LED comes with our unique convenience switch (option) which permits the caregiver to switch to exam mode by simply flipping the top section forward. Installation of a low voltage controller (option) will allow the interface of either the nurse call system or a separate pendant pillow switch (option).

Interior

Patient Room Wall Light

CHRYSALITE LED

## SPECIFICATIONS

### Construction

Extruded Aluminum Housing  
High impact acrylic lens, UV treated, with frosted diffuse coating.

### Source

Nichia LED chips (or equivalent) mounted on linear boards.

### Driver

Roal Strato RSL035-09 or equivalent driver.

### Finish

Polymer powder coat flat white finish; anti-microbial finish (optional)

### Weight

38 lbs (3ft); 50 lbs (4ft)

### Validation

CSA Certified Damp Location (Canada, US)

### Voltage

Multi-volt 120-277V

### Input Wattage

126 watts (top and bottom mode 2u2d configuration 4ft fixture)  
63 watts (top mode 2u2d configuration 4ft fixture)

### Light Output

9000 lumens (top and bottom mode 2u2d configuration 4ft fixture)  
4600 lumens (top mode 2u2d configuration 4ft fixture)

### Dimming

0-10V dimming standard

### Color Quality

>80 CRI

### Life Estimate

40,000 hours\*

\*LED life projection based on IES TM-21 and IES LM-80

### Warranty

Five-year standard LED warranty, terms and conditions apply. (see [www.healthcare-lighting.com](http://www.healthcare-lighting.com))

